VAN PHUOC TAPE JOINT STOCK COMPANY ADD: 1/3 TO KY, AP DONG, THOI TAM THON, HOC MON, HO CHI MINH CITY, VIETNAM TEL: 84-903-817 1137 FAX: 848-371-333097 Email: bangkeovanphuocvn@gmail.com

DATA SHEET SPECIFICATIONS

DESCRIPTION

OPP Packaging Tape is a high tack adhesive tape of biaxially oriented polypropylene film coated with emulsion based acrylic adhesive . It has excellent adhesion and shear resistance to variety carton surfaces.

APPLICATION

- > Medium to heavy carton sealing applications
- > Bundling and strapping
- > Sealing cartons and holding applications with materails that stored in extreme temperture
- > For outdoor storage

PHYSICAL PROPERTIES

	MET	RIC
Product Code		OPP
Backing	BOP	P Film
Adhesive Type	Acrylic	Emulsion
Total Thickness	0.05	0 mm
Film Thickness	0.02	8 mm
Adhesive Thickness	0.02	2 mm
Adhesion to Steel	> 6.3 N	I/25 mm
Adhesion to Fiber	> 6.3 N/25 mm	
Holding Power	Hour < 48	
	AVAILABLE COLOR (S)	
	AVAILABLE	COLOR (S)
TEST METHOD	AVAILABLE	COLOR (S)
TEST METHOD PSTC Method	AVAILABLE Clear Yellow	COLOR (S) Tan
	Clear	Tan
PSTC Method	Clear Yellow	Tan LENGTH (S) m) 100 y (90 m)

Tape should be stored in its original in a cool, dry area away from direct sunlight and should be used within 12 months of date