VAN PHUOC TAPE JOINT STOCK COMPANY

ADD: 1/3 TO KY, AP DONG, THOI TAM THON, HOC MON, HO CHI MINH CITY,

VIETNAM

TEL: 84-903-817 1137 FAX: 848-371-333097 Email: bangkeovanphuocvn@gmail.com

DATA SHEET SPECIFICATIONS

DESCRIPTION

OPP Packaging Tape is a high tack adhesive tape of biaxially oriented polypropylene film coated with emulsion based acrylic adhesive. It has excellent adhesion and shear resistance to variety carton surfaces.

APPLICATION

- > Medium to heavy carton sealing applications
- > Bundling and strapping
- > Sealing cartons and holding applications with materails that stored in extreme temperture
- > For outdoor storage

PHYSICAL PROPERTIES

	METRIC
Product Code	OPP
Backing	BOPP Film
Adhesive Τγρε	Acrylic Emulsion
Total Thickness	0.043 mm
Film Thickness	0.025 mm
Adhesive Thickness	0.018 mm
Adhesion to Steel	> 4.5 N/25 mm
Adhesion to Fiber	> 4.5 N/25 mm
Holding Power	Hour < 48

TEST METHOD

PSTC Method

AVAILABLE COLOR (S)

Clear Yellow

STANDARD WIDTH(S)

2" (48 mm) 2.5" (60 mm) 3" (72 mm)

STANDARD LENGTH (S)

Tan

45 y (40.5 m) 50 y (45 m) 100 y (90 m) 1000 y (900 m)

STORAGE & USAGE CONDITIONS

Tape should be stored in its original in a cool, dry area away from direct sunlight and should be used within 12 months of date

^{**} others sizes and lengths are availble upon request **